



Make it your lifestyle!

WHEN YOU NEED RELIABILITY AND DURABILITY, THE ALLTRACK M3 SERIES NEVER DISAPPOINTS.

The Alltrack M3 and M3-HD Mid-Wheel Drive (MWD) provide the perfect blend of indoor maneuverability and outdoor performance, ideal for active lifestyles. Thanks to the patented dual-action suspension, the M3 enables users to easily navigate everyday obstacles both indoors and out. Each M3 is fully modular and can be equipped with a wide array of positioning and electronic accessories providing exceptional performance and endless possibilities.

ALLTRACK M³



Highlights

- Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption
- Compact turning radius
- Completely modular
- Full selection of power positioning options
- Seat to floor height as low as 15.5" (395 mm)
- Proven, 4-pole German motors
- Multiple frame, drive wheel and caster options
- Available in standard (300 lb weight capacity) and HD (450 lb weight capacity) models

SHOWN IN COBALT BLUE

NOTE: Now available in a new NARROW base option. See pages 4 through 7.





* Add 1.5" (40 mm) when using the HD ALTA Power Seat Elevation module.

1. Subject to variances depending on configuration and manufacturing tolerances.
2. Dimensions listed are for power base only.
3. Custom specialized power seating options available.
4. Contact Customer Service for additional weight information.

Technical Specifications

Configuration	Mid-wheel drive – Standard (Alltrack M3) or Heavy-duty (Alltrack M3-HD)
Suspension system	Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption
Ground clearance ¹	3.5" (90 mm) with a 14" (355 mm) drive wheel, 2.875" (75 mm) with a 12.5" (320 mm) drive wheel
Base width ²	N2221 21" (535 mm) with GP 22 batteries 23.375" (595 mm) with GP 22 batteries N2424 24" (610 mm) with GP 24 batteries Standard 25.375" (645 mm) with GP 24 batteries
Base length ²	35.125" (890 mm)
Base turning radius	20" (510 mm)
Weight capacity	0-300 lb (0-136 kg) M3 0-450 lb (0-205 kg) M3-HD 400 lb (181 kg) for elevating seat on M3-HD
4-Pole motor options	6.5 mph (10 km/h) Std (M3 and M3-HD) 5.4 mph (8.7 km/h) option (M3-HD)
Transit option (Unoccupied)	4-point tie-down brackets (Standard)
Transport option WC-19 (Occupied)	Optional with select seat sizes and seating configurations (Not available with N2221 and N2424 options)
Battery types	Two 12 V, deep cycle Gel cell Group 22NF (50 Ah) or Group 24 (70 Ah)
Battery charger	8 A, off board
Electronics	PG Drives VR2 (non-expandable 90 A) or R-net (expandable 90 A or 120 A)
Assistive driving package	Available with Smart-Track technology (Not available with the N2221 option)
Specialty controls	Compatible with Switch-It, Stealth, ASL or MO-VIS as well as other current systems
Seat width range	Adjustable from 15" to 26" (380 mm to 660 mm) wide (Widths of 23" to 26" not available with the N2221 option)
Power seating options ³	Power Tilt, Power Recline with Mechanical Shear Reduction (MSR), Combination Power Tilt and Recline with MSR, Center Mount Elevating & Articulating Foot Platform, Independent Power Elevating & Articulating Legrests, ALTA 11" Power Seat Elevation
Seat to floor height range (With power tilt or ALTA Power Seat Elevation)*	15.5" to 18.75" (395 mm to 475 mm)
Seat to floor height range (With combo power tilt and ALTA Power Seat Elevation)*	17.5" or 18.25" (445 mm or 465 mm)
Component weights ⁴	N2221 base width 21": 126 lb (57 kg) Compact base width 23.375": 128 lb (58 kg) N2424 base width 24": 137 lb (62 kg) Standard base width 25.375": 133 lb (60 kg) Batteries: Group 22NF: 2 x 36.6 lb (16.6 kg) Group 24: 2 x 54 lb (24.5 kg)
Drive wheel diameter	12.5" or 14" (320 mm or 355 mm)
Caster wheel diameter	6" or 8" (150 mm or 205 mm)

All the capacity of a full size M3 or P3...

N2221

**Narrow Base Option
21" Wide**

mobility 
product award 2023



**ALLTRACK P3 SHOWN IN
SUBLIME**

Available for the
ALLTRACK
M³ P³

Highlights

- 21" Base width with 14" drive wheels – 2.375" narrower than full-size M3 and P3 with GP22 batteries
- Patented dual-action suspension – Same performance and function as full-size M3 and P3
- Full Tilt (50°) and Recline (160°) are available with ALTA 11" Power Seat Elevation
- Available with both Independent Elevating Legrests and Power Center Mount Foot Platform
- Compatible with VR2 (non-expandable) and R-net (expandable) electronics
- No additional cost, simple line-item choice on M3 and P3 order forms
- Seat to floor height as low as 15.5"
- Standard 4-pole, 6.5 mph motors
- Seat sizes up to 22" x 22"
- 14" or 12.5" drive wheels
- Group 22 batteries





1. Subject to variances depending on configuration and manufacturing tolerances.
2. Dimensions listed are for power base only.
3. Custom specialized power seating options available.
4. Contact Customer Service for additional weight information.

Technical Specifications

Configuration	Mid-wheel drive – Standard (Alltrack M3 and P3)
Suspension system	Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption
Ground clearance ¹	3.5" (90 mm) with a 14" (355 mm) drive wheel, 2.875" (75 mm) with a 12.5" (320 mm) drive wheel
Base width ²	21" (535 mm) with GP 22 batteries
Base length ²	35.125" (890 mm)
Base turning radius	20" (510 mm)
Weight capacity	0-300 lb (0-136 kg)
4-Pole motor options	6.5 mph (10 km/h)
Transit option (Unoccupied)	4-point tie-down brackets (Standard)
Transport option WC-19 (Occupied)	N/A
Battery types	Two 12 V, deep cycle Gel cell Group 22NF (50 Ah)
Battery charger	8 A, off board
Electronics	PG Drives VR2 (non-expandable 90 A) or R-net (expandable 90 A or 120 A)
Assistive driving package	N/A
Specialty controls	Compatible with Switch-It, Stealth, ASL or MO-VIS as well as other current systems
Seat width range	Adjustable from 11" to 22" (280 mm to 560 mm) wide
Power seating options ³	Power Tilt, Power Recline with Mechanical Shear Reduction (MSR), Combination Power Tilt and Recline with MSR, Center Mount Elevating & Articulating Foot Platform, Independent Power Elevating & Articulating Legrests, ALTA 11" Power Seat Elevation
Seat to floor height range (With power tilt or ALTA Power Seat Elevation)	15.5" to 18.75" (395 mm to 475 mm)
Seat to floor height range (With combo power tilt and ALTA Power Seat Elevation)	17.5" or 18.25" (445 mm or 465 mm)
Component weights ⁴	N2221 base width 21", 126 lb (57 kg); Batteries: Group 22NF: 2 x 36.6 lb (16.6 kg)
Drive wheel diameter	12.5" or 14" (320 mm or 355 mm)
Caster wheel diameter	6" (150 mm)

Now in a new narrow base option!

N2424

**Narrow Base Option
24" Wide**



**ALLTRACK M3 SHOWN
IN CANDY RED**



Available for the

ALLTRACK

M³ P³

Highlights

- 24" Base Width with 14" drive wheels – 1.375" narrower than full-size M3 with GP24 batteries
- Patented dual-action suspension - Same performance and function as full-size M3
- Available with both Independent Elevating Legrests and Power Center Mount Foot Platform
- Compatible with VR2 (non-expandable) and R-net (expandable) electronics
- Full Tilt (50°) and Recline (160°) are available with ALTA 11" Power Seat Elevation
- No additional cost, simple line-item choice on M3 and P3 order forms
- Group 24 batteries for maximum range
- Seat sizes up to 24" x 22"
- 14" or 12.5" drive wheels
- Seat to floor height as low as 15.5"
- Standard 4-pole, 6.5 mph motors





ALTA 11" POWER SEAT ELEVATION
(Allows for driving in reduced speed while elevated)

1. Subject to variances depending on configuration and manufacturing tolerances.
2. Dimensions listed are for power base only.
3. Custom specialized power seating options available.
4. Contact Customer Service for additional weight information.

Technical Specifications

Configuration	Mid-wheel drive – Standard (Alltrack M3 and P3)
Suspension system	Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption
Ground clearance ¹	3.5" (90 mm) with a 14" (355 mm) drive wheel, 2.875" (75 mm) with a 12.5" (320 mm) drive wheel
Base width ²	24" (610 mm) with GP 24 batteries
Base length ²	35.125" (890 mm)
Base turning radius	20" (510 mm)
Weight capacity	0-300 lb (0-136 kg)
4-Pole motor options	6.5 mph (10 km/h)
Transit option (Unoccupied)	4-point tie-down brackets (Standard)
Transport option WC-19 (Occupied)	N/A
Battery types	Two 12 V, deep cycle Gel cell Group 24 (70 Ah)
Battery charger	8 A, off board
Electronics	PG Drives VR2 (non-expandable 90 A) or R-net (expandable 90 A or 120 A)
Assistive driving package	Available with Smart-Track technology
Specialty controls	Compatible with Switch-It, Stealth, ASL or MO-VIS as well as other current systems
Seat width range	Adjustable from 11" to 24" (280 mm to 610 mm) wide
Power seating options ³	Power Tilt, Power Recline with Mechanical Shear Reduction (MSR), Combination Power Tilt and Recline with MSR, Center Mount Elevating & Articulating Foot Platform, Independent Power Elevating & Articulating Legrests, ALTA 11" Power Seat Elevation
Seat to floor height range (With power tilt or ALTA Power Seat Elevation)	15.5" to 18.75" (395 mm to 475 mm)
Seat to floor height range (With combo power tilt and ALTA Power Seat Elevation)	17.5" or 18.25" (445 mm or 465 mm)
Component weights ⁴	N2424 base width 24", 137 lb (62 kg) Group 24: 2 x 54 lb (24.5 kg)
Drive wheel diameter	12.5" or 14" (320 mm or 355 mm)
Caster wheel diameter	6" or 8" (150 mm or 205 mm)

Rise to a new position!

MODULAR, POWER STANDING ON OUR PROVEN ALLTRACK M3.

The robust and maneuverable Alltrack M3 reaches new levels of function with the addition of our all new, fully adjustable power standing option.*

The **Alltrack M3 Ascent** features a purpose built, independent standing module complemented by power tilt/recline and power articulating center mount foot platform functions in addition to an optional ALTA 11" Power Seat Elevation module. This complete package is now available on a maneuverable mid-wheel drive (MWD) platform.

Retaining the balanced, stable performance of our existing Alltrack M3, the Ascent allows users to drive at a reduced speed while standing and offers the ability to adjust their position to meet physiological and functional needs.

* The use of the standing function can only be prescribed by a medical professional. Introduction to regular standing should be done under the supervision of a qualified therapist.

ALLTRACK M3

Ascent

Highlights

- Mid-wheel drive maneuverability and reliable Alltrack performance
- Fully modular and adjustable system
- Capable of interfacing with a full complement of R-net and specialty drive controls
- 250 lb (115 kg) weight capacity
- Adjustable from 15"-24" wide and 16"-22" deep
- Seat to floor height (STF) as low as 16.75" without ALTA Power Seat Elevation
- Synchronized actuators for a smooth, natural standing motion
- Independently adjustable and removable swing-away knee blocks for functional, less obtrusive look
- ALTA 11" Power Seat Elevation available but not required for standing function



SHOWN IN COBALT BLUE



1. Subject to variances depending on configuration and manufacturing tolerances.
2. Dimensions listed are for power base only.
3. Contact Customer Service for additional weight information.

Technical Specifications


Configuration	Mid-wheel drive with standing function (Alltrack M3 Ascent)
Suspension system	Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption
Ground clearance ¹	3.5" (90 mm) with a 14" (355 mm) drive wheel, 2.875" (75 mm) with a 12.5" (320 mm) drive wheel
Base width ²	25.375" (645 mm)
Base length ²	35.125" (890 mm)
Base turning radius	20" (510 mm)
Weight capacity	0-250 lb (0-114 kg)
4-Pole motor option	6.5 mph (10.5 kmh)
Transit option (Unoccupied)	4-point tie-down brackets (Standard)
Battery type	Two 12 V, deep cycle Gel cell Group 24 (70 Ah)
Battery charger	8 A, off board
Electronics	PG Drives R-net 120A
Assistive driving package	Available with Smart-Track technology
Specialty controls	Compatible with Switch-It, Stealth, ASL or MO-VIS as well as other current systems
Seat width range	Adjustable from 15" to 24" (380 mm to 610 mm) wide
Power seating options	Power Tilt, Power Recline with Mechanical Shear Reduction (MSR), Combination Power Tilt and Recline with MSR, Center Mount Elevating & Articulating Foot Platform, Power Elevating Seat and Power Standing
Seat to floor height range (Without ALTA Power Seat Elevation)	16.75" (425 mm) with 12.5" (320 mm) drive wheel; 17.75" (450 mm) with 14" (355 mm) drive wheel
Seat to floor height range (With ALTA Power Seat Elevation)	18.5" (470 mm) with 12.5" (320 mm) drive wheel; 19.5" (495 mm) with 14" (355 mm) drive wheel
Component weights ³	Base: 133 lb (60 kg) Batteries: Group 24: 2 x 54 lb (24.5 kg)
Drive wheel diameter	12.5" or 14" (320 mm or 355 mm)
Caster wheel diameter	6" or 8" (150 mm or 205 mm)

No compromise!


GET STABILITY, SPEED AND MANEUVERABILITY WITH STATE-OF-THE-ART HYBRID-WHEEL DRIVE TECHNOLOGY.

The **Alltrack R3 and R3-HD Hybrid** are the one and only true Hybrid-Wheel Drive (HWD) power wheelchairs, melding the best attributes of rear-wheel drive and mid-wheel drive in one capable package. HWD is ideal for users that demand the outdoor performance, speed, and comfort of a traditional rear-wheel drive but need the maneuverability provided by mid-wheel drive. By combining unique geometry with patented dual-action suspension, the R3 Hybrid offers a compact, maneuverable base without sacrificing performance!

Choose your footprint



Flared front arms: Standard footprint at the front, similar to mid-wheel drive models.



Straight front arms: Smaller footprint at the front, similar to typical rear-wheel drive models.

ALLTRACK R³ HYBRID



SHOWN IN CANDY RED

Highlights

- Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption
- Stability, speed, comfort, and outdoor performance of rear-wheel drive
- Compact footprint and turning radius of 21.75" (550 mm) provides maneuverability similar to a mid-wheel drive
- Available with center mount articulating foot platform or independent elevating legrests
- Multiple frame, drive wheel and caster options
- Available in standard (300 lb weight capacity) and HD (400 lb weight capacity) models



Technical Specifications

Configuration	Hybrid-wheel drive – Standard (Alltrack R3 Hybrid) or Heavy-duty (Alltrack R3-HD Hybrid)
Suspension system	Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption
Ground clearance ¹	3.5" (90 mm) with a 14" (355 mm) drive wheel, 2.875" (75 mm) with a 12.5" (320 mm) drive wheel
Base width ²	23.375" (595 mm) with GP 22 batteries or 25.375" (645 mm) with GP 24 batteries
Base length ²	35.875" (910 mm)
Base turning radius	21.75" (550 mm)
Weight capacity	0-300 lb (0-136 kg) R3 Hybrid 0-400 lb (0-180 kg) R3-HD Hybrid
4-Pole motor options	6.5 mph (10 km/h) Std (R3/R3-HD Hybrid) 8.5 mph (13.7 km/h) option (R3 Hybrid) max. user weight 250 lb
Transit option (Unoccupied)	4-point tie-down brackets (Standard)
Transport option WC-19 (Occupied)	Optional with select seat sizes and seating configurations
Battery types	Two 12 V, deep cycle Gel cell Group 22NF (50 Ah) or Group 24 (70 Ah)
Battery charger	8 A, off board
Electronics	PG Drives VR2 (non-expandable 90 A) or R-net (expandable 90 A or 120 A)
Assistive driving package	Available with Smart-Track technology
Specialty controls	Compatible with Switch-It, Stealth, ASL or MO-VIS as well as other current systems
Seat width range	Adjustable from 15" to 26" (380 mm to 660 mm) wide
Power seating option ³	Power Tilt, Power Recline with Mechanical Shear Reduction (MSR), Combination Power Tilt and Recline with MSR, Center Mount Elevating & Articulating Foot Platform, Independent Power Elevating & Articulating Legrests, ALTA 11" Power Seat Elevation
Seat to floor height range (With power tilt or ALTA Power Seat Elevation) *	15.75" to 19" (400 mm to 485 mm)
Seat to floor height range (With combo power tilt and ALTA Power Seat Elevation) *	17.75" or 18.5" (450 mm or 470 mm)
Component weights ⁴	For a compact base width 23.375": 127 lb (57 kg); For a standard base width 25.375": 132 lb (59 kg) Batteries: Group 22NF: 2 x 36.6 lb (16.6 kg) Group 24: 2 x 54 lb (24.5 kg)
Drive wheel diameter	12.5" or 14" (320 mm or 355 mm)
Caster wheel diameter	8" or 9" (205 mm or 230 mm)



50° POWER TILT



POWER INDIVIDUAL ELEVATING & ARTICULATING LEGRESTS
(Available in combined and/or synchronized)

* Add 1.5" (40 mm) when using the HD ALTA Power Seat Elevation module.

1. Subject to variances depending on configuration and manufacturing tolerances.
2. Dimensions listed are for power base only.
3. Custom specialized power seating options available.
4. Contact Customer Service for additional weight information.

Let the adventure begin!

EXPLORE THE POSSIBILITIES AND EXPERIENCE THE GREAT OUTDOORS WITH CONFIDENCE.

The Alltrack R3 Outdoor is configured to take full advantage of the unique capabilities of Hybrid-Wheel Drive technology. Our patented, fully independent 6-wheel interactive suspension features unparalleled drive wheel travel to provide a more refined, smoother ride that is made to explore. Paired with extra wide, soft 14" x 4" tires and 9" casters, the award winning rugged R3 and R3-HD boasts superior performance over rough, uneven terrain while offering the indoor maneuverability needed for every day mobility.



Custom Outdoor All-Terrain Configuration with 9" rear casters



Outdoor Ready Hybrid-Wheel Drive Technology

- Award-winning trend-setting design
- 4-pole German motors offer up to 8.5 mph hi-speed performance
- Proven, rugged design
- NEW colors and hydrographic options for a personal touch
- Flared front-end option for caster clearance and added stability

State-of-the-art system



Patented Dual-Action Suspension

Discover the go anywhere capability of our dual-action terrain dampening suspension. The combination of a fully independent 6-wheel interactive suspension with separate vertical shock absorption offers unmatched stability and comfort, and uncompromising performance on uneven ground. Every Alltrack power wheelchair is equipped with this combination and each offers small adjustments for different body shapes and weights to optimize ride characteristics and help reduce fatigue associated with everyday terrain.

Stage 1 – Base

- Fully independent 6-wheel interactive suspension
- Multiple pivot points all lined with bushings for no metal on metal wear and creaking
- Stable geometric design without a mechanical anti-pitch system or locking gas cylinder
- Independent drive wheel and caster movement
- Free vertical movement of drive wheel
- Exceptional traction and forward stability

Stage 2 – Base to Seat Vertical Shock Absorption

- 2.6:1 pitch dampening ratio (for every 2.6° of terrain angle the seat angle only moves $\pm 1^\circ$)
- Proprietary direct vertical shock absorption
- Controlled weight distribution
- All day comfort

Ride with confidence!

NO WORRIES...THE FULL-SUSPENSION HD3 MID-WHEEL DRIVE POWER CHAIR IS THE SMOOTHEST RIDE IN TOWN.

The **Alltrack HD3 Mid-Wheel-Drive** is a versatile, fully capable, very heavy-duty (VHD) power wheelchair with a standard weight capacity of up to 550 lb (250 kg). Purpose built to address the unique needs of larger users, the HD3 offers uncompromising performance and capability. Superior indoor maneuverability is possible due to the compact, mid-wheel drive footprint and excellent comfort and stability thanks to patented dual-action suspension.

ALLTRACK HD³



SHOWN IN INDIGO BLUE

Highlights

- Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption tuned for heavier users
- Up to 550 lb weight capacity with full power positioning ranges; 45° of VHD tilt, 160° of VHD power recline and center mount elevating & articulating foot platform
- Extremely compact turning radius of 20.5" (520 mm)
- High-performance, 5.4 mph 4-pole German motors
- Seat to floor height as low as 17" with VHD power tilt and recline



45° VHD POWER TILT

1. Subject to variances depending on configuration and manufacturing tolerances.
2. Dimensions listed are for power base only.
3. Custom specialized power seating options available.
4. Contact Customer Service for additional weight information.

Technical Specifications

Configuration	Bariatric Mid-wheel drive – Very Heavy-Duty (Alltrack HD3)
Suspension system	Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption
Ground clearance ¹	3.5" (90 mm)
Base width ²	27.375" (695 mm)
Base length ²	35.125" (890 mm)
Base turning radius	20.5" (520 mm)
Weight capacity	Up to 550 lb (250 kg)
4-Pole motor options	5.4 mph (8.7 km/h)
Transit option (Unoccupied)	4-point tie-down brackets (Standard)
Battery type	Two 12 V, deep cycle Gel cell Group 24 (70 Ah)
Battery charger	8 A, off board
Electronics	PG Drives VR2 (non-expandable 90 A) or R-net (expandable 90 A or 120 A)
Assistive driving package	Available with Smart-Track technology
Specialty controls	Compatible with Switch-It, Stealth, ASL or MO-VIS as well as other current systems
Seat width range	Adjustable from 19" to 28" (485 mm to 710 mm) wide (Custom seat sizes are available)
Power seating options ³	Bariatric CG Power Tilt, Power Recline with Mechanical Shear Reduction (MSR), Combination Power Tilt and Recline with MSR, Very HD Power Center Mount Elevating & Articulating Foot Platform, VHD Independent Power Elevating & Articulating Legrests
Seat to floor height range (with power tilt)	17" to 19" (430 mm to 485 mm)
Component weights ⁴	For a wide base width 27.375": 133 lb (60 kg) Batteries: Group 24: 2 x 54 lb (24.5 kg)
Drive wheel diameter	14" (355 mm)
Caster wheel diameter	8" (205 mm)

Small but mighty!

THE ALLTRACK P3 (MWD VERSION) HAS THE CAPABILITY AND DURABILITY OF OUR FULL-SIZE M3 BUT CAN BE CONFIGURED WITH SMALLER USERS IN MIND.

Built on our proven and tough M3 base, the **Alltrack P3 Mid-Wheel Drive (MWD)** is designed to give children the capability to explore and thrive, keeping up with whatever comes their way. Our patented dual-action suspension is uniquely configured for lighter users providing the full benefit of the design for optimal stability, vibration dampening, performance and comfort.

This P3 base is configured to provide more compact base widths without sacrificing battery sizes to ensure they always have enough power to enjoy a full day. The compact, mid-wheel drive design provides excellent maneuverability and intuitive driving while boasting a full complement of power positioning options.

ALLTRACK P3

Highlights

- Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption tuned for lighter users
- 4-pole German motors provide a smooth, responsive ride with speeds up to 6.5 mph
- Versatile and compact for indoor and outdoor activities
- Full complement of R-net electronics, specialty controls and Smart-Track available
- Wide array of power positioning available including ALTA 11" Power Seat Elevation with ability to drive while elevated
- Base widths as narrow as 21" without sacrificing battery size or capability
- Seat to floor height as low as 15.5"
- Seat sizes: 11" x 11" adjustable to 16" x 16" with larger and combined ranges available up to 20" wide and 19" deep



**MWD SHOWN IN BUBBLE
GUM METALLIC**

NOTE: Now available in a new NARROW base option. See pages 4 through 7.





50° POWER TILT



ALTA 11" POWER SEAT ELEVATION
(Allows for driving in reduced speed while elevated)

1. Subject to variances depending on configuration and manufacturing tolerances.
2. Dimensions listed are for power base only.
3. Custom specialized power seating options available.
4. Contact Customer Service for additional weight information.

Technical Specifications

Configuration	Pediatric Mid-wheel drive (Alltrack P3 MWD)
Suspension system	Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption
Ground clearance ¹	3.5" (90 mm) with a 14" (355 mm) drive wheel, 2.875" (75 mm) with a 12.5" (320 mm) drive wheel
Base width ²	N2221 21" (535 mm), Standard 23.375" (595 mm) or N2424 24" (610 mm)
Base length ²	35.125" (890 mm)
Base turning radius	20" (510 mm)
Weight capacity	0-300 lb (0-136 kg)
4-Pole motor options	6.5 mph (10 km/h)
Transit option (Unoccupied)	4-point tie-down brackets (Standard)
Transport option WC-19 (Occupied)	Optional with select seat sizes and seating configurations (Not available with the N2221 and N2424 options)
Battery types	Two 12 V, deep cycle Gel cell Group 22NF (50 Ah) or Group 24 (70 Ah)
Battery charger	8 A, off board
Electronics	PG Drives VR2 (non-expandable 90 A) or R-net (expandable 90 A or 120 A)
Assistive driving package	Available with Smart-Track technology (Not available with N2221 option)
Specialty controls	Compatible with Switch-It, Stealth, ASL or MO-VIS as well as other current systems
Effective seat width range	Adjustable from 11" to 20" (290 mm to 510 mm) wide
Power seating options ³	Power Tilt, Power Recline with Mechanical Shear Reduction (MSR), Combination Power Tilt and Recline with MSR, Center Mount Elevating & Articulating Foot Platform, Independent Power Elevating & Articulating Legrests, ALTA 11" Power Seat Elevation
Seat to floor height range (With power tilt or ALTA Power Seat Elevation)	15.5" to 18.75" (395 mm to 475 mm)
Seat to floor height range (With combo power tilt and ALTA Power Seat Elevation)	17.5" or 18.25" (445 mm or 465 mm)
Component weights ³	N2221 base width 21": 126 lb (57 kg) Compact base width 23.375": 128 lb (58 kg) N2424 base width 24": 137 lb (62 kg) Batteries: Group 22NF: 2 x 36.6 lb (16.6 kg) Group 24: 2 x 54 lb (24.5 kg)
Drive wheel diameter	12.5" or 14" (320 mm or 355 mm)
Caster wheel diameter	6" or 8" (150 mm or 205 mm)

Watch them go!

HYBRID-WHEEL DRIVE TECHNOLOGY PROVIDES STABILITY, SPEED AND COMFORT IN A COMPACT, MANEUVERABLE PACKAGE BUILT FOR ADVENTURE.

The **Alltrack P3 Hybrid-Wheel Drive** (HWD) is the one and only hybrid power chair built specifically for smaller users. The P3 HWD offers speeds up to 8.5 mph for high-speed exploring and our patented 6-wheel interactive suspension is specially tuned to provide unsurpassed capability for lighter users. All this performance is complemented by the compact footprint of our hybrid technology to provide excellent indoor maneuverability and comfort.



HWD SHOWN IN SUBLIME

ALLTRACK P3

Highlights

- Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption tuned for lighter users
- Multiple 4-pole German motors available providing a smooth, responsive ride with a speed option up to 8.5 mph
- Versatile hybrid-wheel drive configuration for indoor and outdoor activities
- Full complement of R-net electronics, specialty controls and Smart-Track available
- Wide array of power positioning available including ALTA 11" Power Seat Elevation with ability to drive while elevated
- Base widths as narrow as 23.375" without sacrificing battery size or capability
- Seat to floor height as low as 15.5"

Technical Specifications

Configuration	Pediatric Hybrid-wheel drive (Alltrack P3 HWD)
Suspension system	Patented Dual-Action Suspension: Fully independent 6-wheel interactive suspension with vertical shock absorption
Ground clearance ¹	3.5" (90 mm) with a 14" (355 mm) drive wheel, 2.875" (75 mm) with a 12.5" (320 mm) drive wheel
Base width ²	23.375" (595 mm)
Base length ²	35.875" (910 mm)
Base turning radius	21.75" (550 mm)
Weight capacity	0-300 lb (0-136 kg)
4-Pole motor options	6.5 mph (10 km/h) Std 8.5 mph (13.7 km/h) option maximum user weight 250 lb
Transit option (Unoccupied)	4-point tie-down brackets (Standard)
Transport option WC-19 (Occupied)	Optional with select seat sizes and seating configurations
Battery type	Two 12 V, deep cycle Gel cell Group 22NF (50 Ah)
Battery charger	8 A, off board
Electronics	PG Drives VR2 (non-expandable 90 A) or R-net (expandable 90 A or 120 A)
Assistive driving package	Available with Smart-Track technology
Specialty controls	Compatible with Switch-It, ASL or MO-VIS as well as other current systems
Seat width range	Adjustable from 11" to 20" (290 mm to 510 mm) wide
Power seating options ³	Power Tilt, Power Recline with Mechanical Shear Reduction (MSR), Combination Power Tilt and Recline with MSR, Center Mount Elevating & Articulating Foot Platform, Independent Power Elevating & Articulating Legrests, ALTA 11" Power Seat Elevation
Seat to floor height range (With power tilt or ALTA Power Seat Elevation)	15.75" to 19" (400 mm to 485 mm)
Seat to floor height range (With combo power tilt and ALTA Power Seat Elevation)	17.75" or 18.5" (450 mm or 470 mm)
Component weights ⁴	For a compact base width 23.375": 127 lb (57 kg) Batteries: Group 22NF: 2 x 36.6 lb (16.6 kg)
Drive wheel diameter	12.5" or 14" (320 mm or 355 mm)
Caster wheel diameter	8" or 9" (205 mm or 230 mm)



50° POWER TILT



ALTA 11" POWER SEAT ELEVATION
(Allows for driving in reduced speed while elevated)

1. Subject to variances depending on configuration and manufacturing tolerances.
2. Dimensions listed are for power base only.
3. Custom specialized power seating options available.
4. Contact Customer Service for additional weight information.

Intuitive control today, with an eye to the future...

ENGINEERED FOR EVERYDAY INTUITIVE FUNCTION AIMED AT BENEFITING PROVIDERS, CLINICIANS, TECHNICIANS AND USERS.

Don't let the compact shape of our **e-bx** seat function controller fool you, it packs a powerful amount of function and capability and has been designed with the future in mind. The proprietary architecture of our **e-bx** and **iQ actuators** interface seamlessly with the entire line of R-net electronics and offer true plug-n-play flexibility. Thanks to a unique handshake protocol, these devices are in constant interaction, exchanging vital information such as position, running time, speeds, errors and more. This innovative system offers easily programmable memory seating capabilities as well as error detection for excellent troubleshooting capability and a better overall user experience.

Highlights

- Available on every Alltrack model
- Intuitive plug-n-play functionality
- Compact, slim chassis for unobtrusive mounting
- Fully programmable using existing R-net programming tools
- Control and programming of up to 6 iQ actuators
- Technician friendly troubleshooting features and design
- Built with industry standard 9-pin plug for interfacing popular switches and components


Keypad and R-net Joystick with 3.5" screen



5 Toggle switch keypad




5 Push-button keypad



Memory Power Seating

Technical Specifications

- Program positions of up to 5 functions including tilt, recline, ALTA Power Seat Elevation, 90° power center mount elevating and articulating foot platform or independent elevating legrests, and standing
- Save up to 5 individual memory settings/combinations of seat function
- Memory seating can be programmed and controlled through the wheelchair's drive controls or a separate keypad
- Each function can be latched, individually programmable within separate profiles, not a "global" setting, allowing for more customization
- Two or more actuators can move at the same time for smoother operation and quicker achievement of desired setting



Add color to your world!



Choose your color

1. Onyx Black Matte
2. Indigo Blue
3. Cabernet
4. Cobalt Blue
5. Habanero Metallic
6. Bubble Gum Metallic
7. Sublime
8. Candy Red



Custom hydrographic colors

9. Desert digital camo
10. Woodland camo
11. Carbon fiber





Our values

HUMANITY is the heart of our company.

We have a deep respect and great compassion for human beings inside and outside our organization. We believe in people and we are committed to help.

INTEGRITY is the foundation of our business.

We are proud to work together openly with honesty, ethics and transparency through our daily interactions with our customers, colleagues and partners. We respect employment equity where everyone can contribute their very best.

INNOVATION is the essence of our vision.

We are continuously moving forward, learning, improving, challenging the status quo by encouraging our employees to pursue new ideas that make a difference.

EXCELLENCE is the goal in our performance.

It is the main driver in achieving our objectives. We believe this excellence highlights our leadership and firm determination to provide the best solution for each customer.

PASSION is the source of our creativity.

We share our motivation and commitment to energize, engage and inspire others. We all have a common purpose which is to provide the best customer experience and enjoy doing it.



Life is unpredictable... your mobility device shouldn't be

**OUR MISSION IS TO IMPROVE
CUSTOMER MOBILITY AND
QUALITY OF LIFE BY DEVELOPING A
SUPERIOR PRODUCT AND OFFERING
UNBEATABLE SERVICE TO MEET THE
SPECIFIC NEEDS OF USERS.**



For more information:



1.450.424.0288

1.888.453.0311

info@amylor.com

www.amylor.com



Caution: Federal law restricts this device to sale by or on the order of a practitioner licensed by the law of the Province in which they practice.

BR | PD-A20602 | 1002408 | R03